










LARGE CAPACITY FREESTANDING PHARMACY FRIDGE GLASS DOOR 600L WHITE



- 
+2°C to +8°C Operating Temperature Range
 Conforms to MHRA guidelines.
- 
NEW Advanced Controller
 Records temperatures accurate to 0.1°C.
- 
USB Data Logging
 Allows user to accurately monitor temperature.
- 
Audible Warning Alarms
 Alerts user should internal temperature deviate from set parameters or in the event of a power failure.
- 
Fitted Lock as Standard
 Maintains security and ensures the unit can only be accessed by approved personnel.
- 
Fitted Castors (Lockable)
 For ease of movement.
- 
Fitted with 5 Adjustable Wire Shelves
 Enables optimum air flow inside the unit.


www.facebook.com/Lec-Medical

www.twitter.com/Lec_Medical

SKU CODE:	PRODUCT CODE:	DESCRIPTION:
444440365	PGR600UK	Large Capacity Freestanding Pharmacy Fridge Glass Door 600L White



FULL SPECIFICATION – PGR600UK LARGE CAPACITY FREESTANDING PHARMACY FRIDGE GLASS DOOR 600L WHITE



Description	Freestanding
SKU code	444440365
GDPA code	PGR600UK
Gross capacity (litres)	600
Unit external dimensions (mm) (WxDxH)	690 x 840 x 1995
Packed dimensions (mm) (WxDxH)	840 x 990 x 2195
Product weight (kg)	140
Packed weight (kg)	155
Country of origin	UK
Internal dimensions (mm) (WxDxH)	560 x 680x 1230
Temperature range	+2°C to +8°C
Colour	White/green
External finish	White
Internal finish	Stainless steel
Type of plastic	SRL800 (HIPS/ABS Mix)
Door finish	Painted stainless steel
Door type	Glass
Door style	Hinged
Door open depth	1145
Lock	Yes
Adjustable feet (number & position)	Fitted castors
Temperature display on panel	Yes
Air Temperature alarm	Yes (Audio & Visual)
Mains failure alarm	Yes (Audio & Visual)
Load alarm delay (with no delay)	Yes (Audio & Visual)
Door open alarm	Yes (Audio & Visual)
Compressor alarm	Yes (Visual)
Air/Load/Defrost sensor fail alarm	Yes (Visual)
Battery low alarm	Yes (Visual)
Number of shelves	5
Number of shelf positions	20
Shelf size (WxD)	530 x 650
Shelf material	Plastic coated wire
Interior light	Yes
Fan	Yes
Spark free	No
Auto or manual defrost	Automatic
Controller type	Digital, external
Refrigerant type	R134a
Climate Class	ST
Software interface	Yes
CFC free	Yes
HFC free	Yes
HCFC free	Yes
Ammonia free	Yes
UK 3 pin plug	Yes
Other plug types available	Yes
Voltage supply	230
Aux output	Yes
USB data logging	Yes
Insulation thickness (mm)	60
Insulation type	Cyclopentane
Optional drawer system available	No