



LARGE CAPACITY FREESTANDING PHARMACY FRIDGE SOLID DOOR 1200L WHITE



- +2°C to +8°C Operating Temperature Range**
 Conforms to MHRA guidelines.
- NEW Advanced Controller**
 Records temperatures accurate to 0.1°C.
- USB Data Logging**
 Allows user to accurately monitor temperature.
- Audible Warning Alarms**
 Alerts user should internal temperature deviate from set parameters or in the event of a power failure.
- Fitted Lock as Standard**
 Maintains security and ensures the unit can only be accessed by approved personnel.
- Fitted Castors (Lockable)**
 For ease of movement.
- Fitted with 10 Adjustable Wire Shelves**
 Enables optimum air flow inside the unit.

www.facebook.com/Lec-Medical
www.twitter.com/Lec_Medical

SKU CODE:	PRODUCT CODE:	DESCRIPTION:
444440368	PSR1200UK	Large Capacity Pharmacy Fridge Solid Door 1200L White



FULL SPECIFICATION – PSR1200UK LARGE CAPACITY FREESTANDING PHARMACY FRIDGE SOLID DOOR 1200L WHITE



Description	Freestanding
SKU code	444440368
GDPA code	PSR1200UK
Gross capacity (litres)	1200
Unit external width (mm)	1330
Unit external depth (mm)	840
Unit external height (mm)	1995
Product weight (kg)	200
Packed width (mm)	1480
Packed depth (mm)	990
Packed height (mm)	2195
Packed weight (kg)	220
Country of origin	UK
Internal dimensions (mm) (WxDxH)	1220 x 653 x 1386
Temperature range	+2°C to +8°C
Colour	White/green
External finish	White
Internal finish	Stainless steel
Type of plastic	SRL800 (HIPS/ABS Mix)
Door finish	Painted stainless steel
Door type	Solid
Door style	Hinged
Door open depth	1145
Lock	Yes
Adjustable feet (number & position)	Fitted castors
Temperature display on panel	Yes
Air Temperature alarm	Yes (Audio & Visual)
Mains failure alarm	Yes (Audio & Visual)
Load alarm delay (with no delay)	Yes (Audio & Visual)
Door open alarm	Yes (Audio & Visual)
Compressor alarm	Yes (Visual)
Air/Load/Defrost sensor fail alarm	Yes (Visual)
Battery low alarm	Yes (Visual)
Number of shelves	10
Number of shelf positions	40
Shelf size	645 x 523
Shelf material	Plastic coated wire
Interior light	No
Fan	Yes
Spark free	No
Auto or manual defrost	Automatic
Controller type	Digital, external
Refrigerant type	R134a
Climate Class	ST
CFC free	Yes
HFC free	Yes
HCFC free	Yes
Ammonia free	Yes
UK 3 pin plug	Yes
Other plug types available	Yes
Voltage supply	230
Aux output	Yes
Insulation thickness (mm)	60
Insulation type	Cyclopentane
Optional drawer system available	No