

Ambu® WhiteSensor WS/RT

ECG Electrode - Single use



Actual Size

Key Benefits

- Highly conductive solid gel
- MR Conditional
- Radiolucent
- Strong adhesion
- Comfortable foam backing

Ambu® WhiteSensor WS/RT

The Ambu WhiteSensor WS/RT features a highly conductive solid gel with strong adhesion to ensure a good signal quality during short-term ECG monitoring applications. The graphite connector is radiolucent making it suitable for use with X-ray imaging.

No need for removal & subsequent replacement of electrodes during X-ray procedures. Thanks to the flexible foam backing material, the electrode ensures ease of use and comfort during application.



Solid gel



Foam backing



Radiolucent



MR Conditional

WhiteSensor

Ambu
Ideas that work for life

Specifications

Dimensions	
Electrode size (W x L in mm)	36 x 40
Skin contact size (W x L in mm)	36 x 40
Adhesive area (in mm ²)	857
Height excluding connector/wire (in mm)	1,1
Sensor	
Sensor material	Silver/silver chloride
Gel system	Solid
Sensor area (in mm ²)	79
Gel area/measuring area (in mm ²)	201
Electrical data (ANSI/AAMI)	
AC impedance - typical	150 Ω
DC offset voltage - typical	1 mV
Defibrillation overload recovery - typical	12 mV
Rate of change of polarization potential - typical	0.3 mV/s
Combined offset instability and internal noise	9 µV
Bias current tolerance (over 8 hours)	5 mV
Environment	
PVC-free electrode	Yes
Electrode not made with natural rubber latex	
PVC-free packaging	Yes
X-Ray & MRI	
Radiolucent	Yes
MR Conditional	Yes**
Shelf lifeS	
Opened pouches	30 days
Unopened pouches	24 months*

*from date of production

Materials

Electrode		Standard Packaging		Options	
Bio-compatible	Yes	Quantity/pouch	50	Connectors	S
Sensor	Silver/silver chloride (Ag/AgCl)	Quantity/box	600/7200	Pre-wired	-
Outer carrier	Polyethylene foam (PE)			Pre-wired connectors	-
Outer adhesive	Polyacrylate				
Connector (stud)	Carbon				
Liner	Polyester (PET)				
Precaution					
Single use only					

Available configurations

Reference number	Units/card	Units/pouch	Units/inner box	Units/outer box
WS-oo-S/RT/50	1	50	600	7200

** Static magnetic field of 1.5 Tesla and 3 Tesla only. Maximum spatial gradient field of 10.000 Gauss/cm or 100 Tesla/m. Maximum whole body averaged specific absorption rate (SAR) of 2 W/kg for 15 minutes of scanning.

■ Product

WS-oo-S ■ Wire length (cm)
■ Connector

Ambu Ltd.

8 Burrel Road
St Ives
Cambridgeshire
PE27 3LE

Tel 01480 498403
Fax 01480 498405
uksales@ambu.com
www.ambu.co.uk

CE US: Rx only